



US007699267B2

(12) **United States Patent**
Helou, Jr.

(10) **Patent No.:** **US 7,699,267 B2**
(45) **Date of Patent:** **Apr. 20, 2010**

- (54) **CARGO AIRCRAFT**
- (75) Inventor: **Elie Helou, Jr.**, Carpinteria, CA (US)
- (73) Assignee: **Biosphere Aerospace, LLC**,
Carpinteria, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 247 days.

(21) Appl. No.: **11/782,850**

(22) Filed: **Jul. 25, 2007**

(65) **Prior Publication Data**
US 2009/0026314 A1 Jan. 29, 2009

Related U.S. Application Data
(62) Division of application No. 10/996,799, filed on Nov. 23, 2004, now Pat. No. 7,261,257.

- (51) **Int. Cl.**
B64C 1/22 (2006.01)
- (52) **U.S. Cl.** **244/137.1; 244/1 R**
- (58) **Field of Classification Search** 244/1 R,
244/137.1, 137.2; 220/4.33; 414/800
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
- | | | | | |
|-------------|---------|--------------|-------|-----------|
| 2,053,969 A | 9/1936 | Olds | | 220/1.5 |
| 2,095,440 A | 10/1937 | Hojnowski | | 224/118.1 |
| 2,388,380 A | 11/1945 | Bathurst | | 224/118.2 |
| 2,407,774 A | 9/1946 | Fowler | | 224/118 |
| 2,425,499 A | 8/1947 | Watter | | 224/118.3 |
| 2,425,972 A | 8/1947 | Watter | | 244/118.3 |
| 2,876,969 A | 3/1959 | Tydon et al. | | 244/118.3 |
| 2,931,681 A | 4/1960 | Keller | | 254/2 R |
| 3,009,672 A | 11/1961 | Tharratt | | 244/137.1 |
| 3,028,130 A | 4/1962 | Burton | | 244/137.1 |
| 3,055,620 A | 9/1962 | Weiland | | 244/135 A |
| 3,147,942 A | 9/1964 | Griffith | | 244/18.3 |


3,150,849 A	9/1964	Hugh et al.	244/100 R
3,209,929 A	10/1965	Petersen	414/676
3,289,981 A	12/1966	Meyer	244/137.2
3,368,838 A	2/1968	Reich	294/82.24
3,381,921 A	5/1968	McDonough	410/79
3,419,164 A	12/1968	O'Neill	414/345
3,691,595 A	9/1972	Backteman et al.	24/287
3,872,555 A	3/1975	Link et al.	24/590.1
3,966,285 A	6/1976	Porch et al.	312/265.4
3,972,427 A	8/1976	Stanley et al.	244/137.1
4,301,984 A	11/1981	Olason	244/137.1
4,379,533 A	4/1983	Caldwell et al.	244/118.1
5,238,102 A	8/1993	Langer	206/3
5,240,207 A	8/1993	Eiband et al.	244/190
5,816,425 A	10/1998	Keip et al.	220/4.31
5,975,464 A	11/1999	Rutan	244/120
6,494,404 B1	12/2002	Meyer	244/118.2
6,817,579 B2	11/2004	Van Der Velden et al.	244/137.2
7,000,765 B2	2/2006	Hase et al.	206/503
2005/0247824 A1	11/2005	Allison	244/137.2
2006/0022090 A1	2/2006	McCoskey et al.	244/137.1
2006/0038077 A1	2/2006	Olin et al.	244/137.1
2006/0108477 A1	5/2006	Helou	244/137.1

Primary Examiner—Timothy D Collins
(74) *Attorney, Agent, or Firm*—Connolly Bove Lodge & Hutz LLP

(57) **ABSTRACT**

An aircraft for carrying at least one rigid cargo container includes a beam structure with a forward fuselage attached to the forward end of the beam structure and an empennage attached to the rearward end of the beam structure. Wings and engines are mounted relative to the beam structure and a fairing creates a cargo bay able to receive standard sized intermodal cargo containers. Intermodal cargo containers of light construction and rigid structure are positioned within the cargo bay and securely mounted therein. The beam structure is designed to support flight, takeoffs and landings when the aircraft is empty but requires the added strength of the containers securely mounted to the beam structure when the aircraft is loaded. The aircraft is contemplated to be a drone.

5 Claims, 15 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 6




Fig. 5




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 13




Fig 12




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




FIG. 26




FIG. 27




Fig. 28




FIG. 29




FIG. 30

CARGO AIRCRAFT**CROSS-REFERENCE TO RELATED APPLICATION**

This application is a divisional of prior application Ser. No. 10/996,799, filed Nov. 23, 2004.

BACKGROUND OF THE INVENTION

The field of the present invention is cargo aircraft for transporting modular containers.

The basic unit for transporting goods has been the truck. Being the basic unit, the truck has defined limitations on intermodal containers that can typically be transported by ships, trains and trucks. Much of commerce today for which intermodal containers are most convenient are high volume, low weight products, computers being one example. Thus, volume instead of weight creates the limiting factor in the design of intermodal containers. As such, containers have grown to the maximum volume capacity of the basic unit, the truck. As such, intermodal containers are limited by the dimensions allowed by highway infrastructures.

The aforementioned intermodal containers have greatly facilitated and lowered the cost of cargo transportation. However, air cargo has generally been excluded from participation in intermodal cargo systems. Aircraft of a size capable of carrying substantial cargo have typically been designed first as passenger aircraft. Cylindrical fuselages and lack of large access ports thereto in such passenger aircraft limit the use of such aircraft for truly intermodal cargo systems. Rather, the aircraft must become the basic unit with odd shaped and smaller sized containers. As a result, even with containerized cargo, a truck must be loaded with multiple individual containers for efficient distribution of air cargo. Such aircraft are also designed to be efficient at high speeds which is costly. Military transports are also not particularly compatible with intermodal cargo systems as they are designed for oversized cargo such as rolling equipment, e.g., tanks and trucks, and palletized, irregularly shaped cargo. Most aircraft specifically designed for the military also are mission directed and overall efficiency for competitive cargo transportation is not a first priority.

The inability of aircraft to participate in intermodal container cargo systems has been disadvantageous to international commerce. Business principals such as just-in-time supply and changing business environments including rapid global internet communication have created a demand for much more rapid international shipping than can be provided by conventional ships. However, air cargo systems remain both expensive and inconvenient to intermodal shipping.

SUMMARY OF THE INVENTION

The present invention is directed to an aircraft having a beam structure to receive at least one rigid cargo container with mounts detachably integrating the at least one rigid cargo container as part of the beam structure to provide structural rigidity to the aircraft in flight.

In a first separate aspect of the present invention, the aircraft includes a forward fuselage and an empennage attached to either end of the beam structure. Wings and engines are also provided.

In a second separate aspect of the present invention, the mounts associated with the beam structure are located on the top side of the beam structure to detachably support at least one rigid container thereon.

In a third separate aspect of the present invention, the mounts are on the underside of the beam structure to detachably suspend at least one rigid cargo container therefrom.

In a fourth separate aspect of the present invention, the at least one rigid cargo container is the size of an intermodal container and is of a composite lightweight structure.

In a fifth separate aspect of the present invention, multiple containers and orientations thereof are contemplated.

In a sixth separate aspect of the present invention, an empennage is constructed to provide direct access longitudinally to the beam from the back of the aircraft.

In a seventh separate aspect of the present invention, a forward fuselage is pivotally associated relative to the beam to allow full access to the forward end of the beam.

In an eighth separate aspect of the present invention, the aircraft is a drone. As a drone, efficient low speed and, correspondingly, longer flights without crew are cost effective and advantageous.

In a ninth separate aspect of the present invention, a forward fuselage, an empennage, wings and engines are each removable as separate units from association with the beam.

In a tenth separate aspect of the present invention, a method is disclosed for providing low-cost and efficient transportation of intermodal cargo containers to a desired destination. The method comprises providing a drone aircraft, loading the intermodal cargo containers onto the drone aircraft, and causing the drone aircraft to fly at efficient low speeds to the desired destination.

In a eleventh separate aspect of the present invention, the drone aircraft comprises a forward fuselage, an empennage, wings, and a beam structure including a first end to which the forward fuselage is attached and a second end to which the empennage is attached.

In a twelfth separate aspect of the present invention, the method further comprises the step of detachably mounting at least one intermodal cargo container to the beam structure before the step of causing the aircraft to fly.

In a thirteenth separate aspect of the present invention, the method further comprising the step of attaching adjacent intermodal cargo containers to structurally engage one another before the step of causing the aircraft to fly.

In a fourteenth separate aspect of the present invention, the intermodal cargo containers have sufficient structure and rigidity that bending and torsional forces experienced by the beam structure are in part borne by the intermodal cargo containers when the drone aircraft is in flight.

In a fifteenth separate aspect of the present invention, any of the foregoing separate aspects are contemplated to be combined to greater advantage.

Accordingly, it is an object of the present invention to provide an improved cargo aircraft. Other and further objects and advantages will appear hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a first embodiment of an aircraft.

FIG. 2 is a partial perspective view with portions broken away for clarity of the aircraft of FIG. 1.

FIG. 3 is a cross-sectional view taken transversely through the fuselage of the aircraft of FIG. 1.

FIG. 4 is a perspective view of a cargo bay and combinations of containers.

FIG. 5 is a partial exploded perspective view of the aircraft of FIG. 1.

FIG. 6 is a detailed perspective of the fuselage of the aircraft of FIG. 5.

FIG. 7 is a side view of a fairing frame for the aircraft of FIG. 1 with a container in place.

FIG. 8 is a perspective view of the aircraft of FIG. 1 being loaded or unloaded.

FIG. 9 is a perspective view of the aircraft of FIG. 1 with the forward fuselage raised.

FIG. 10 is a perspective view of a frame structure of a cargo container.

FIG. 11 is a perspective view of a longer frame structure of a cargo container.

FIG. 12 is a perspective view of an exploded assembly of a cargo container.

FIG. 13 is a partial cross-sectional view of a panel illustrated in FIG. 12.

FIG. 14 is a detail cross-sectional view of an assembled panel on a cargo container.

FIG. 15 is a cross-sectional view of a mount between the beam structure and a container.

FIG. 16 is an exploded perspective view of corner attachments and couplers.

FIG. 17 is a perspective view of a second embodiment of an aircraft.

FIG. 18 is a partial perspective view of the aircraft of FIG. 17 with portions broken away for clarity.

FIG. 19 is a cross-sectional view taken transversely of the fuselage of the aircraft of FIG. 17.

FIG. 20 is a perspective view of an aircraft with cargo containers side by side.

FIG. 21 is a cross-sectional view of the fuselage of the aircraft of FIG. 20.

FIG. 22 is a cross-sectional view as in FIG. 21 with an amended beam configuration.

FIG. 23 is a partial perspective view of the aircraft of FIG. 20 with portions broken away for clarity.

FIG. 24 is a perspective view of a fourth embodiment of an aircraft.

FIG. 25 is a partial perspective view of the aircraft of FIG. 24 with portions broken away for clarity.

FIG. 26 is a cross-sectional view of the fuselage of the aircraft of FIG. 24.

FIG. 27 is a cross-sectional view of the fuselage of yet another embodiment.

FIG. 28 is a perspective view of an aircraft of a further embodiment.

FIG. 29 is a partial side view of the fairing frame of FIG. 7 with a first attachment rail system.

FIG. 30 is a partial side view of the fairing frame of FIG. 7 with a second attachment rail system.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 illustrates a first aircraft design with an integrating and supporting beam structure 30 having two ends. The details of the beam structure 30 are better illustrated in FIGS. 2 and 3. The beam structure 30 includes a floor 32 which may include rollers and/or antifriction devices to facilitate longitudinal movement of a cargo container along the surface of the floor 32. Restraining flanges 33 run along each longitudinal side of the floor 32. In addition to the floor 32, the beam structure 30 includes I-beams 34 with bulkheads 36, 38 positioned periodically along the beam structure 30 and affixed to the floor 32 and the I-beams 34. The beam structure 30 becomes a rigid structure which is preferably sufficient to support the aircraft in flight when empty but cannot support the aircraft in flight when loaded.

A forward fuselage 40 is located at one end of the beam structure 30. The forward fuselage 40 is shown to be that of a drone with no cockpit. Since the Shuttle SRTM mapping mission, it has been possible to have extended commercial flights without human intervention. A cargo drone can fly at low speeds for long distances without concern for crew time and passenger fatigue. The aircraft can therefore be designed for highly efficient flight profiles without accommodation for crew and passengers.

As illustrated in FIG. 9, the forward fuselage 40 is pivotally mounted relative to the beam structure 30 to fully expose the interior cavity above the beam structure 30 from the forward end of the aircraft for loading of cargo containers. The guidance and control for the aircraft may be located in the forward fuselage 40; but, given the lack of a cockpit, can be located elsewhere with equal facility. The forward fuselage 40 may be removed from association with the beam as a unit.

An empennage 42 is attached to the other end of the beam structure 30. The empennage 42 includes laterally extending horizontal stabilizers 44 with twin vertical stabilizers 46 positioned at the outer ends of the horizontal stabilizers 44. As illustrated in FIG. 8, the rear fuselage 48 forming part of the empennage 42 may be split vertically and pivotally mounted to either side of the main fuselage. In this way, access is provided to the rear end of the beam structure 30 across the ramp defined by the empennage 42 including the horizontal stabilizers 44. The empennage 42 may be removed from association with the beam as a unit.

Wings 50 are also structurally associated with the beam structure 30. The wings 50 as well as the beam structure 30 may contain fuel tanks. Landing gear 52 are provided under the wings 50; and a forward gear 54 is provided under the beam structure 30. The wings 50 may be removed from association with the beam as a unit.

Engines 56 are shown in the embodiment of FIG. 1 to be directly mounted to the beam structure 30. An engine on each side, symmetrically mounted, is contemplated. Alternatively, as illustrated in FIG. 28, the engines 56 are mounted atop the wings 50. This arrangement is understood to add to the efficiency of the aircraft. The engines 56 may each be removed from association with the beam as a unit.

FIGS. 5 and 6 illustrate framing to support aerodynamic panels. The frame includes vertical elements 58 and horizontal elements 60 with corner elements 62 lying in transverse planes of the aircraft. One such frame 63 is illustrated in greater detail in FIGS. 7, 29 and 30. These elements 58, 60 are typically of I-beam cross section with lightening holes as in conventional aircraft construction. Corner elements 64 extend longitudinally at the intersections of the vertical elements 58 and horizontal elements 60. These corner elements 64 may provide structural rigidity to augment the strength of the beam structure 30 and certainly provide sufficient rigidity to retain fairing components in place on the frame 62. In FIG. 5, a top fairing panel 66 and a side fairing panel 68 are shown. Of course, a second side fairing panel 68 is also deployed on the other side of the aircraft.

The aircraft thus defined provides a cargo bay which is designed and sized to closely receive rigid cargo containers 70 forming right parallelepipeds which are the sizes of intermodal containers. Such intermodal containers are typically of a given height and width and varying incrementally in length. An alternative to the construction of a fairing to define a cargo bay between the forward fuselage 40 and the empennage 42 would be to define the intermodal containers with aerodynamic surfaces. The forward fuselage 40 and the empennage 42 would transition to create an aerodynamic surface with the forward fuselage 40 and the empennage 42. The containers 70

would be designed to be compatible with truck transportation whether or not they have aerodynamic surfaces.

In the embodiments, the rigid cargo containers **70** provide strength to the beam structure **30**. The beam structure **30** is designed to be as light as possible. As such, the beam structure **30** is capable of supporting takeoff loads, flight loads and landing loads of the aircraft when free of cargo. Additionally, the beam structure **30** must be sufficient to support compression loads upon landing even when fully loaded. However, the beam structure **30** is not required to fully sustain bending and torsional loads in flight, landing and takeoff when a rigid cargo container or multiple such containers are in place in the aircraft. The additional rigidity required is supplied by the rigid cargo containers **70**. To this end, the containers **70** are constructed with sufficient structure and rigidity and are securely mounted to the beam structure **30** such that bending and torsional forces experienced by the beam structure **30** are imposed upon the securely mounted container or containers **70**.

Mounts **72** are provided on the beam structure **30**. These mounts may be bolted or otherwise retained on the floor **32**. Further, incremental adjustments are preferably provided in order that the mounts **72** can attach to the container or containers **70** while accommodating variations in container length and placement. Such incremental adjustment may be provided by patterns of attachment holes in the floor **32** to allow for lateral or longitudinal repositioning of the mounts **72** once the container or containers **72** are in place. A mount **72** is illustrated in FIG. **15** as a shoulder bolt **72** which extends between the beam structure **30** and a container **70**. Such a bolt **72** provides substantial shear resistance as well as tension loading. The mounts **72** may be located or positionable along the full length of the floor **32** or at incremental positions reflecting standard container sizes. The mounts may face inwardly from the sides of the floor **32**. Access ports through the fairings may be provided to allow access to the mounts **72**. Alternatively, mechanisms may be employed which are automatic or remotely actuated.

Attachments **74** are illustrated in FIG. **16** as formed boxes **76** through which slots **78** extend. By employing the formed boxes **76**, the slots **78** terminate to provide an inner face. The attachments **74** are located in the structure of the rigid container or containers **70**. As such, the attachments **74** cooperate with the formed boxes **74** with slots **76** through the walls thereof. The formed boxes **76** may include thick walls on one outer side or bottom to receive the mounts **72**.

To fix the attachments **74** to one another, couplers **84** are employed. Each coupler **84** includes two heads **86** extending in opposite directions from a coupler body **88**. The heads **86** are undercut between the body **88** and each of the heads **86** to form opposed engaging surfaces on the inner sides of the heads **86**. The heads **86** also fit within the slots **76** in one orientation. The heads **86** have a convex surface for easier placement in the associated slots **76**.

The couplers **84** may be formed such that the heads **86** are on a shaft rotatable within the body **88**. A collar **90** is separated from each of the heads **86** by substantially the thickness of the walls of the formed boxes **76** with the collar **90** being of sufficient diameter that the collar **90** cannot fit within the slots **78**. The collar **90** also provides access once the heads **86** are positioned in the slots **78** for rotation of the heads **86** into a locked orientation with the slots **78**. The body **88** is of sufficient size and includes flat sides **92** such that it is prevented from rotating by the floor **32**. Once the head **86** have been properly located, a set screw **94** can be placed to insure that

the heads **86** will not rotate relative to the attachments **74**. The same mechanisms are employed between attachments **74** on adjacent containers **70**.

The mounts **72** may correspond to the attachments **74** and employ the same mechanisms as shown in FIG. **16**. Identical slots **78** in the floor **32** or the restraining flanges **33** can cooperate with the slots **78** in the containers **70** and couplers **84** to restrain the containers **70** and integrate the structures thereof with the beam structure **30**.

Each rigid cargo container **70** is constructed as shown in FIGS. **10** through **16**. A first internal structure of a container is illustrated in FIG. **10**. This structure includes four columns **96** and eight beams **98** fixed together by corner attachments **74** as illustrated in FIG. **10** to form a right parallelepiped. Panels **100** are then assembled with longerons **102** to form a top, a bottom and sides of the cargo container **70**. A representative panel **100** is illustrated in FIG. **13**. The panel **100** is formed of lightweight material. In this embodiment the panel **100** is defined by two thin sheets **104**, **106** separated by honeycomb **108**. Inner longerons **110** are also placed between the sheets **104**, **106** and attached thereto. About the periphery of each of the panels **100**, the sheets **104**, **106** come together to form an attachment flange **112**. Each of these panels **100** may be of composite material or a mixture of aluminum sheets **104**, **106** and formed honeycomb **108**.

FIG. **13** illustrates the sides, top and bottom of the completed cargo container **70** in association with the structure defined by the four columns **96** and eight beams **98**. Two panels **100** are associated together with longerons **102** positioned therebetween. The attachment flanges **112** are fixed to the corner columns **96** and beams **98** which include parallel flanges **114** for that purpose.

Where longer containers are contemplated, intermediary columns **96** and beams **98** may additionally be employed. In this way, all panels **100** may be of the same size through appropriate location of the columns **96** with the overall lengths of the containers being multiples of the container illustrated in FIG. **10**. Multiple containers of varying length may be employed to create an overall payload for an aircraft of a given length. FIG. **4** illustrates such arrangements with a sixty-foot long cargo area and containers **70** broken into various multiples of ten-foot lengths.

FIG. **8** illustrates employment of the first embodiment through the placement of a cargo container **70**. A truck **116** is shown aligned with the cargo area of the aircraft. In this case, the rear fuselage **48** is defined by doors which extend in an aerodynamic form and can also open to fully expose the interior of the fairing for insertion or removal of the rigid cargo container **70**. This container **70** may be, as illustrated in FIG. **4**, one single container or a preassembled group of containers **70**. Winches and other mechanisms may be employed to assist in the repositioning of the container or containers **70** either in the aircraft or on the truck **116**. Alternatively, the forward fuselage **40** may be pivoted out of the way as illustrated in FIG. **9** and the container **70** loaded from or unloaded to the truck **116** from the front of the aircraft. The landing gear **52** and/or forward gear **54** may be additionally extendable or retractable or the mounts thereof may be able to move up and down to accommodate the level of the bed of a truck **116**.

The general principles described herein with regard to the first embodiment also apply to the several other embodiments which are presented. A second embodiment is illustrated in FIGS. **17** through **19**. In this embodiment, the beam structure **30** is arranged at the top of the aircraft with the rigid cargo container or containers **70** suspended thereunder through attachments to the underside of the beam structure **30**. In this

7

second embodiment, the beam structure is effectively inverted and is formed of a very similar structure to that of the first embodiment. The wings **50** are correspondingly associated with the top of the aircraft to be at the beam structure for support. Further, the engines **56** are also so located.

This repositioning of the beam structure **30** makes the loading and unloading of containers through the empennage **42** more difficult. However, the forward fuselage **40** continues to provide loading capability through rotation of the forward fuselage **40** out of the way. Alternatively, cargo bay doors **118**, as illustrated in FIG. **19**, may provide access for loading of the container or containers **70** from below. To accommodate this overhead placement of the beam structure **30**, the landing gear **52** must be supported at a greater distance than as required in the first embodiment. Either the gear **52**, **54** itself or structure **119** may extend within additional fairings **120** to either side of the fuselage.

FIGS. **20** through **23** illustrate another configuration having a double-wide beam structure **30** to accommodate side-by-side rigid cargo containers **70**. But for the dimensional changes and required additional structural rigidity within the beam structure **30**, the foregoing discussion applies to this embodiment. FIGS. **21** and **22** show two different configurations of the I-beams **34** to support different expected weight requirements. These figures also illustrate a central column disposed between the side by side containers which can be a bulkhead or a series of independent columns. Alternatively, the side by side containers **70** can be linked together as discussed above and the containers **70** at or adjacent that joint also attached to mounts associated with the central corner element **64** with no central column present.

FIGS. **24** through **26** illustrate yet another embodiment designed to accommodate a different arrangement of rigid cargo containers **70**. In this embodiment, two-high sets of containers are placed side by side to achieve four times the cross-sectional area for container cargo as in the first embodiment. The same comments applied to FIGS. **21** and **22** regarding the central column, illustrated between the containers **70** in FIG. **26**, apply to this embodiment.

FIG. **27** provides a hybrid between the first and second embodiments. Two sets of side-by-side cargo containers **70** are positioned above and below the beam structure **30**. The same comments applied to FIGS. **21** and **22** regarding the central column, illustrated between the containers **70** in FIG. **27**, apply to this embodiment.

FIGS. **29** and **30** illustrate yet another feature which can augment the structure of the system. A rail **122** is associated

8

with the frame **62** in two locations as illustrated in the two figures. A corresponding channel **124** is shown located in the container **70**. The channel **124** may be an interlocking fit as shown only at the corners of the container **70** or fully through the container with additional support provided therealong. The rail mechanism is shown in association with the fairing but may be associated with the beam structure **30** as well.

Thus, improved cargo aircraft have been disclosed. While embodiments and applications of this invention have been shown and described, it would be apparent to those skilled in the art that many more modifications are possible without departing from the inventive concepts herein. The invention, therefore is not to be restricted except in the spirit of the appended claims.

What is claimed is:

1. A method for providing low-cost and efficient transportation of intermodal cargo containers to a desired destination, the method comprising:

providing a drone aircraft comprising a supporting beam structure;

integrating the intermodal cargo containers with the beam structure of the drone aircraft, the intermodal cargo containers providing the structural rigidity to the beam structure to support the drone aircraft in flight; and causing the drone aircraft to fly at efficient low speeds to the desired destination.

2. The method of claim **1**, wherein the drone aircraft further comprises a forward fuselage, an empennage, wings, and the beam structure including a first end to which the forward fuselage is attached and a second end to which the empennage is attached.

3. The method of claim **2**, further comprising the step of detachably mounting at least one intermodal cargo container to the beam structure before the step of causing the aircraft to fly.

4. The method of claim **3**, further comprising the step of attaching adjacent intermodal cargo containers to structurally engage one another before the step of causing the aircraft to fly.

5. The method of claim **4**, wherein the intermodal cargo containers have sufficient structure and rigidity that bending and torsional forces experienced by the beam structure are in part borne by the intermodal cargo containers when the drone aircraft is in flight.

* * * * *